

Philips BX250U

[Philips; Eindhoven \(tubes international!\); Miniwatt](#)

- **Country**
- [Netherlands](#)
- **Year**
- 1955/1956

Number of Tubes 5

- **Valves / Tubes**

- [UCH42 UF41 UBC41 UL41 UY42](#)

- **Main principle**

- Superheterodyne (common); ZF/IF 452 kHz; 2 AF stage(s)

- **Tuned circuits**

- 6 AM circuit(s)

- **Wave bands**

- Broadcast, Long Wave and Short Wave.

- **Power type and voltage**

- AC/DC-set / 110-127; 220 Volt

- **Loudspeaker**

- Permanent Magnet Dynamic (PDyn) Loudspeaker (moving coil) / Ø 10 cm = 3.9 inch

- **Material**

- Bakelite case

- Model: **BX250U** - Philips; Eindhoven tubes

- **Shape**

- Tablemodel without push buttons, Mantel/Midget/Compact up to 14

- **Dimensions (WHD)**

- 295 x 190 x 150 mm / 11.6 x 7.5 x 5.9 inch

- **Notes**

- AM radio with built-in ferroceptor:

- LW: 150 - 261 kHz.
- BC: 517 - 1622 kHz.
- SW: 5,94 - 18,2 MHz.

- **Net weight (2.2 lb = 1 kg)**

- 2.5 kg / 5 lb 8.1 oz (5.507 lb)

